Docket No. AUS9-2000-0316-US1

PERMANENT OPEN FIRMWARE PCI HOST BRIDGE (PHB) UNIT ADDRESSING TO SUPPORT DYNAMIC MEMORY MAPPING AND SWAPPING OF I/O DRAWERS

BACKGROUND OF THE INVENTION

1. Technical Field:

The present invention relates generally to the field of computer software and, more specifically, to a method, system, and apparatus for managing addressing to input/output drawers.

2. Description of Related Art:

A logical partitioning option (LPAR) within a data processing system (platform) allows multiple copies of a single operating system (OS) or multiple heterogeneous operating systems to be simultaneously run on a single data processing system platform. A partition, within which an operating system image runs, is assigned a non-overlapping sub-set of the platform's resources. These platform allocable resources include one or more architecturally distinct processors with their interrupt management area, regions of system memory, and input/output (I/O) adapter bus slots. The partition's resources are represented by its own open firmware device tree to the OS image.

Each distinct OS or image of an OS running within the platform is protected from each other such that software errors on one logical partition can not affect the correct operation of any of the other partitions. This is provided by allocating a disjoint set of platform

resources to be directly managed by each OS image and by providing mechanisms for ensuring that the various images can not control any resources that have not been allocated to it. Furthermore, software errors in the control of an OS's allocated resources are prevented from affecting the resources of any other image. Thus, each image of the OS (or each different OS) directly controls a distinct set of allocable resources within the platform.

In many systems, I/O devices are incorporated into the data processing system using I/O drawers. These I/O drawers are modular structures that are easy to install and remove allowing for easy modification of the data processing system. The I/O drawers typically contain several I/O expansion slots in which I/O devices may be "plugged" into and used by the data processing system. For example, many I/O drawers allow for 8 or 16 I/O expansion slots.

Each I/O drawer and expansion slot within the I/O drawer must be assigned addresses by the data processing system such that input and output requests from various components within the system may utilize the new hardware. In prior art RIO systems, open firmware peripheral component interconnect (PCI) Host Bridge (PHB) unit addresses are dynamically generated based on dynamic discovery of PHBs on successive Remote Input/Output (RIO) loop probes. A RIO system employs a special I/O bridge, which is called an RIO hub and has several ports to connect to I/O drawers via special high-speed cables. An I/O drawer has two ports. There are two typical RIO loops: 1) one port of a hub connected to the input port

of an I/O drawer, and the output port of this I/O drawer connected to the companion port of the same hub; 2) one port of a hub connected to the input port of an I/O drawer, the output port of this I/O drawer connected to the input port of another I/O drawer, and the output port of the other I/O drawer connected to the companion port of the same hub. An RIO loop probe refers to the discovery process to determine the presence of one of these two RIO loops. The ODM of some operating systems, such as, for example, Advanced Interactive Executive (AIX) operating system, use the open firmware device path (e.g. /pci@fba0000000/scsi) as the identifier of an Object Database Management (ODM) object. ODM is a software component of AIX. Hardware functional components such as PCI Host Bridges (PHBs) are represented as ODM objects in the database to be managed by the ODM software. If a user moves an RIO drawer from one RIO loop to another, all open firmware PHB unit addresses change. The AIX ODM then presents the user with questions regarding the disappearance of the associated resources for the "old" drawer and the appearance of resources associated with a "new" drawer, when, from the user's point of view, all of the same resources are still being employed. Currently, the user must manually resolve the AIX ODM when the drawer is moved to a different location within the same data processing system.

Such occurrences can be confusing and annoying to users, therefore, a data processing system in which I/O drawers may be inserted, removed, and rearranged without requiring a user to resolve any address problems would be

desirable.

SUMMARY OF THE INVENTION

The present invention provides a method, system, and apparatus for managing input/output drawers within a data processing system. In one embodiment, a unique location identifier is assigned to each of a plurality of input/output drawers. The unique location identifier is stored in memory and is used by the operating system to identify the plurality of input/output drawers regardless of how the input/output drawers are interconnected by cables. When a new input/output drawer is added to the data processing system, the service processor assigns a new unique location identifier to the new input/output drawer ensuring that the unique location identifiers previously assigned to other I/O drawers are not used to identify the new I/O drawer.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 depicts a block diagram of a data processing system in which the present invention may be implemented;

Figure 2 depicts a block diagram of an exemplary logically partitioned platform in which the present invention may be implemented;

Figure 3 depicts a block diagram of a system for installing and managing a system I/O drawers in accordance with the present invention;

Figure 4 depicts a flowchart illustrating an exemplary process for incorporating a new I/O drawer into a data processing system in accordance with the present invention; and

Figure 5 depicts a flowchart illustrating an exemplary process for assigning memory mapping to I/O drawers in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, and in particular with reference to **Figure 1**, a block diagram of a data processing system in which the present invention may be implemented is depicted. Data processing system **100** may be a symmetric multiprocessor (SMP) system including a plurality of processors **101**, **102**, **103**, and **104** connected to system bus **106**. For example, data processing system **100** may be an IBM RS/6000, a product of International Business Machines Corporation in Armonk, New York, implemented as a server within a network. Alternatively, a single processor system may be employed. Also connected to system bus **106** is memory controller/cache **108**, which provides an interface to a plurality of local memories **160-163**. I/O bus bridge **110** is connected to system bus **106** and provides an interface to I/O bus **112**. Memory controller/cache **108** and I/O bus bridge **110** may be integrated as depicted.

Data processing system **100** is a logically partitioned data processing system. Thus, data processing system **100** may have multiple heterogeneous operating systems (or multiple instances of a single operating system) running simultaneously. Each of these multiple operating systems may have any number of software programs executing within in it. Data processing system **100** is logically partitioned such that different I/O adapters **120-121**, **128-129**, **136,** and **148-149**

may be assigned to different logical partitions.

Thus, for example, suppose data processing system **100** is divided into three logical partitions, P1, P2, and P3. Each of I/O adapters **120-121**, **128-129**, **136**, and **148-149**, each of processors **101-104**, and each of local memories **160-164** is assigned to one of the three partitions. For example, processor **101**, memory **160**, and I/O adapters **120**, **128**, and **129** may be assigned to logical partition P1; processors **102-103**, memory **161**, and I/O adapters **121** and **136** may be assigned to partition P2; and processor **104**, memories **162-163**, and I/O adapters **148-149** may be assigned to logical partition P3.

Each operating system executing within data processing system **100** is assigned to a different logical partition. Thus, each operating system executing within data processing system **100** may access only those I/O units that are within its logical partition. Thus, for example, one instance of the Advanced Interactive Executive (AIX) operating system may be executing within partition P1, a second instance (image) of the AIX operating system may be executing within partition P2, and a Windows 2000 operating system may be operating within logical partition P1. Windows 2000 is a product and trademark of Microsoft Corporation of Redmond, Washington.

Peripheral component interconnect (PCI) Host bridge **114** connected to I/O bus **112** provides an interface to PCI local bus **115**. A number of Input/Output adapters **120-121** may be connected to PCI bus **115**. Typical PCI bus implementations will support between four and eight I/O

~~adapters (i.e. expansion slots for add in connectors).~~ Each I/O Adapter **120-121** provides an interface between data processing system **100** and input/output devices such as, for example, other network computers, which are ~~clients to data processing system **100**.~~

~~An additional PCI host bridge **122** provide an~~ interface for an additional PCI bus **123**. PCI bus **123** is connected to a plurality of PCI I/O adapters **128-129** by a PCI bus **126-127**. Thus, additional I/O devices, such as, for example, modems or network adapters may be supported through each of PCI I/O adapters **128-129**. In this manner, data processing system **100** allows connections to ~~multiple network computers.~~

A memory mapped graphics adapter **148** may be connected to I/O bus **112** through PCI Host Bridge **140** and EADS **142** (PCI-PCI bridge) via PCI buses **141** and **144** as depicted. Also, a hard disk **150** may also be connected to I/O bus **112** through PCI Host Bridge **140** and EADS **142** via PCI buses **141** and **145** as depicted.

~~A PCI host bridge **130** provides an interface for a~~ PCI bus **131** to connect to I/O bus **112**. PCI bus **131** connects PCI host bridge **130** to the service processor mailbox interface and ISA bus access pass-through logic **194** and EADS **132.** The ISA bus access pass-through logic **194** forwards PCI accesses destined to the PCI/ISA bridge **193.** The NV-RAM storage is connected to the ISA bus **196**. The Service processor **135** is coupled to the service processor mailbox interface **194** through its local PCI bus **195**. Service processor **135** is also connected to ~~processors **101-104** via a plurality of JTAG/I^2C buses **134**.~~

JTAG/I^2C buses **134** are a combination of JTAG/scan busses (see IEEE 1149.1) and Phillips I^2C busses. However, alternatively, JTAG/I^2C buses **134** may be replaced by only Phillips I^2C busses or only JTAG/scan busses. All SP-ATTN signals of the host processors **101**, **102**, **103**, and **104** are connected together to an interrupt input signal of the service processor. The service processor **135** has its own local memory **191**, and has access to the hardware op-panel **190**.

When data processing system **100** is initially powered up, service processor **135** uses the JTAG/scan buses **134** to interrogate the system (Host) processors **101-104**, memory controller **108**, and I/O bridge **110**. At completion of this step, service processor **135** has an inventory and topology understanding of data processing system **100**. Service processor **135** also executes Built-In-Self-Tests (BISTs), Basic Assurance Tests (BATs), and memory tests on all elements found by interrogating the system processors **101-104**, memory controller **108**, and I/O bridge **110**. Any error information for failures detected during the BISTs, BATs, and memory tests are gathered and reported by service processor **135**.

If a meaningful/valid configuration of system resources is still possible after taking out the elements found to be faulty during the BISTs, BATs, and memory tests, then data processing system **100** is allowed to proceed to load executable code into local (Host) memories **160-163**. Service processor **135** then releases the Host processors **101-104** for execution of the code loaded into Host memory **160-163**. While the Host

processors **101-104** are executing code from respective operating systems within the data processing system **100**, service processor **135** enters a mode of monitoring and reporting errors. The type of items monitored by service processor include, for example, the cooling fan speed and operation, thermal sensors, power supply regulators, and recoverable and non-recoverable errors reported by processors **101-104**, memories **160-163**, and bus-bridge controller **110**.

Service processor **135** is responsible for saving and reporting error information related to all the monitored items in data processing system **100**. Service processor **135** also takes action based on the type of errors and defined thresholds. For example, service processor **135** may take note of excessive recoverable errors on a processor's cache memory and decide that this is predictive of a hard failure. Based on this determination, service processor **135** may mark that resource for deconfiguration during the current running session and future Initial Program Loads (IPLs). IPLs are also sometimes referred to as a "boot" or "bootstrap".

Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 1** may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect to the present invention.

~~With reference now to **Figure 2**, a block diagram of an exemplary logically partitioned platform is depicted~~

~~in which the present invention may be implemented. The~~ hardware in logically partitioned platform **200** may be implemented as, for example, server **100** ~~in~~ **Figure 1**. Logically partitioned platform **200** includes partitioned hardware **230**, Open Firmware (OF) **210**, and operating systems **202-208**. Operating systems **202-208** may be multiple copies of a single operating system or multiple heterogeneous operating systems simultaneously run on ~~platform 200.~~

~~Partitioned hardware 230 includes a plurality of~~ processors **232-238**, a plurality of system memory units **240-246**, a plurality of input/output (I/O) adapters **248-262**, and a storage unit **270**. Each of the processors **242-248**, memory units **240-246**, NV-RAM storage **298**, and I/O adapters **248-262** may be assigned to one of multiple partitions within logically partitioned platform **200**, each of which corresponds to one of operating systems ~~202-208~~.

OF **210** performs a number of functions and services for operating system images **202-208** to create and enforce the partitioning of logically partitioned platform **200**. Firmware is "software" stored in a memory chip that holds its content without electrical power, such as, for example, read-only memory (ROM), programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), and non-volatile random access memory (non-volatile RAM).

OF **210** is a firmware implemented virtual machine identical to the underlying hardware. Thus, OF **210** allows the simultaneous execution of independent OS

images **202-208** by virtualizing all the hardware resources of logically partitioned platform **200**. OF **210** may attach I/O devices through I/O adapters **248-262** to single virtual machines in an exclusive mode for use by one of OS images **202-208**.

With reference now to **Figure 3**, a block diagram of a system for installing and managing a system I/O drawers is depicted in accordance with the present invention. System **300** may be implemented within a data processing system such as, for example, logically partitioned platform **200** in **Figure 2**. A system I/O drawer is a modular component for inserting I/O expansion slots into a data processing system. An I/O drawer physically packages several PHBs to provide PCI I/O slots for plug-in I/O adapters. In **Figure 1**, everything attached to I/O bus **112** could reside in an I/O drawer, including the service processor **135**. The I/O bus **112** is a special high-speed cable connecting the I/O bridge **110**, which is called a hub, to the I/O drawer's input/output ports. The I/O drawer containing the service processor **135** is called the primary drawer. All other I/O drawers are connected via the System Power Control Network (SPCN) bus **380** to the service processor **135**.

System **300** includes three I/O drawers **304-308**. Each of I/O drawers **304-308** contains two PCI host bridges (PHBs) **310-320**. However, although depicted with three I/O drawers **304-308** and two PHBs **310-320**, one skilled in the art will recognize that more or fewer I/O drawers and PHBs may be included than depicted in **Figure 3**. Each PHB **310-320** may support, for example, between 8 and 16 PCI

expansion slots, which may be implemented, for example, as I/O adapters **248-262** in **Figure 2**.

Service processor **302**, which may be implemented, for example, as service processor **290** in **Figure 2**, assigns a unique SPCN ID to each of I/O drawers **304-308** within the system **300**. Service processor uses the SPCN bus to detect and assign unique IDs to I/O drawers, to control the power logic of the I/O drawers, and to monitor their environmental sensors such as drawer temperature, fan speed, etc. The SPCN ID is then associated with the drawer's unique serial number from the drawer's Vital Product Data (VPD). The VPD contains information related to the product in which it is found such as, for example, product manufacturer, product serial number, and part number. When a new drawer is added to system **300**, service processor **302** changes the SPCN ID of the new drawer to a value not being used by any of the existing I/O drawers **304-308**. An SPCN/SN table **324** within NVRAM **322** is updated by service processor **302** to reflect the new assignment of the SPCN ID. NVRAM **322** may be implemented as, for example, NVRAM **298** in **Figure 2**. The SPCN/SN table **324** is used in determining if a new I/O drawer is installed since the new I/O drawer's serial number is not in the existing table. From the SPCN/SN table **324**, the service processor **302** can find out all SPCN Ids currently used by the existing I/O drawers **304-308** so that it can select an unused SPCN ID for the new drawer. The SPCN ID can be used to label an I/O drawer by displaying its SPCN ID to the I/O drawer LCD operator panel.

System firmware **326**, which may be implemented as open firmware **210** in **Figure 2**, dynamically discovers the I/O drawers **304-308** and assigned memory mapping to each one of drawers **304-308** and its PHBs **310-320**. The location code for the drawer, in one embodiment, is U0.X where X is the SPCN ID of the drawer **304-308**. Firmware **326** also creates PHB nodes with the "reg" property. The "reg" property is an open firmware device node property that indicates the unit address of the PHB device with respect to the address space of the parent device node, which is the system root node. In one embodiment, the PHB nodes have the following form: MMMPSSSS SSSSSSSS, where MMM is the RIO drawer type. For example, MMM = 0x800 for Outlaw drawer and 0x400 for Outlaw-X drawer. P is the PHB number within the drawer, i.e. 0, 1, or 2. SSSS SSSSSSSS is the low order six bytes of the drawer's VPD Serial Number (SN) keyword data. VPD SN keyword data is the content of the SN field within the Vital Product Data.

Firmware **326** also creates location codes for PHB nodes as, for example, U0.X-P1 where X is the SPCN ID of the drawer. The device nodes and location codes are stored in open firmware (OF) device tree **342** within system memory **340**. System memory **340** may be implemented as, for example, memory **191** in **Figure 1**. The PHB nodes are parts of the open firmware device tree **342** constructed by open firmware in system memory **340.** Since the serial number and SPCN ID are permanently associated and maintained by service processor **302**, the ODM of the OS, such as, for example, one of OSs **202-208**, will be

unchanged for the drawer. AIX Object Database Management (ODM) software allows users to query and manage system configuration.

If one of I/O drawers **304-308** is removed from system **300** and used in another data processing system, the SPCN of the I/O drawer may be reprogrammed by the new system such that a new SN/SPCN association is established for the ODM of the OS on the new system. If the operator panel FRU of the I/O drawer where the VPD is kept is replaced during servicing, the socketed VPD module may be retained and used in the new operator panel ~~set~~ so that the service action does not affect the operating systems ODM. If one of the I/O drawers **304-308** is moved to a different physical location within system **300**, no action on the part of the user is required. This movement of drawers is transparent to the customer. Thus, OF PHB unit addresses (used as operating system ODM "handles", which is a key to be used in the ODM database search) are permanent for a given RIO drawer even if the drawer is moved to a new RIO loop and given a new memory mapping. Consequently, the AIX ODM object for the drawer is the same regardless of location. The PHB unit address is the "reg" property of the PHB device node in the OF device tree.

Those of ordinary skill in the art will appreciate that the components depicted in **Figure 3** may vary. For example, other I/O adapters may be utilized rather than PCI type adapters. The depicted example is not meant to imply architectural limitations with respect to the present invention.

With reference now to **Figure 4**, a flowchart

illustrating an exemplary process for incorporating a new I/O drawer into a data processing system is depicted in accordance with the present invention. After a new I/O drawer, such as, for example, one of I/O drawers **304-308** is inserted into a data processing system, the service processor recognizes that a new drawer has been installed (step **402**). The service processor then consults an SPCN/SN table of assignments of SPCN IDs to existing I/O drawers to ensure that the new I/O drawer is not assigned an SPCN previously assigned to another I/O drawer (step **404**). The service processor then changes the new I/O drawer's SPCN ID to one not being used by one of the existing I/O drawers (step **406**). The SPCN/SN table is then updated to reflect the new assignment (step **408**).

With reference now to **Figure 5**, a flowchart illustrating an exemplary process for assigning memory mapping to I/O drawers is depicted in accordance with the present invention. As I/O drawers, such as, for example, one of I/O drawers **304-308** in **Figure 3**, are added to a data processing system, the system firmware, such as, for example, firmware **326** in **Figure 3**, discovers the I/O drawers (step **502**). The firmware then assigns memory mapping to the I/O drawer and each of its associated PHBs (step **504**). Memory mapping to an I/O drawer as used herein means assigning system memory address ranges so that these addresses can be used by the host processors to access I/O devices within the drawer. SPCN ID is not involved in the memory mapping process. SPCN ID is used by open firmware to generate PHB location codes for the PHB nodes in the device tree. The firmware then creates PHB nodes (step **506**) and location codes for the PHB nodes

(step **508**) and stores this information in the open firmware device tree (step **510**) located in system memory, such as, for example, system memory **340** in **Figure 3**. Each PHB node's "reg" property is the PHB's unit address. PHB nodes are device representation of the PHB hardware in the open firmware device tree. The nodes contain the open firmware device properties which describe the characteristics of the PHBs and the memory mapping of the PHBs, and open firmware methods which are software device driver function for the PHBs.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media such a floppy disc, a hard disk drive, a RAM, and CD-ROMs and transmission-type media such as digital and analog communications links.

The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of

ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.